



# RAZOR 16M

A NEW ERA OF EMERGENCY MONITORING AND TESTING



## FEATURES

- Slimblade recessed exit
- 200 × 100 mm decal size
- Single and double sided decals
- Compliant emergency exit sign
- Best in class energy consumption
- Rod / surface / suspended or wall mounted
- High Quality Lithium battery (LiFePO<sub>4</sub>) and smart charger



## WIRELESS UPGRADE

Automatically test and sync data to the Cloud



## DALI CERTIFIED

Connect to a DALI system for DALI testing




## SELF TEST

Commission the product to perform its own tests



## SINGLE POINT UNIT

Ektor products work as SPUs out of the box



## PRODUCT RANGE

ORDER CODE	QTY
<b>EV-RAZOR-16M</b> Slimblade Emergency Exit	4
<b>EV-RAZOR-16M-B</b> Black Slimblade Emergency Exit	4

## FEATURES

- Long life electronics
- Slimblade recessed exit
- Single and double sided decals
- Compliant emergency exit sign
- Best in class energy consumption
- High ambient temperature rating (40°C)
- High Quality Lithium battery (LiFePO<sub>4</sub>) and smart charger

## ACCESSORY RANGE

ORDER CODE	DESCRIPTION
<b>EV-RAZOR-16M-RM-DECAL</b>	Razor Decal Pack 1xright, 1xleft and 1xstraight
<b>EV-RAZOR-LEDFIRE-SM-KIT</b>	Surface Mount Kit
<b>EV-RAZOR-LEDFIRE-SM-KIT-B</b>	Surface Mount Kit, black
<b>EV-RODMOUNT-WHT</b>	Rod mount, incl. bracket for roof /body
<b>EV-RODMOUNT-BLACK</b>	Rod mount, incl.bracket for roof /body, black
<b>EV-WIREDBYCLICK-2.4M-F&amp;P</b>	Wire By Click 5-Pin Lead L1025/5, 2.4M
<b>EV-WIELAND-2.4M-F&amp;P</b>	Wieland Plug GST1815S B1 ZR1 S PB02, 2.4M
<b>EV-CMS-2.4M-5PIN</b>	CMS 5 Pin Plug Set, 2.4M
<b>EV-WAGO-2.4M-F&amp;P</b>	WAGO Plug 5-P Blue 51110475, 2.4M
<b>EV-CMS-2.4M-6PIN</b>	CMS 6 Pin Plug Set, 2.4M
<b>EV-DALI-JB</b>	DALI Cable and Junction box, 2.4M
<b>ZC-BATT-1500MAH</b>	zencontrol 1500mAH 6.4V 2 Cell LiFePO <sub>4</sub> Battery
<b>ZC-WIFI</b>	zencontrol Wi-Fi Expansion Module

## OPERATIONAL INFORMATION

### GENERAL

Voltage	220~240V
Frequency	50Hz
Ambient temp.	0 - 40°C
Class	2
Wiring	Terminal block (1-16 mm □)
Mounting type	Recessed (rod / surface / suspended accessories)
IP rating	IP20
Decal size	200 × 100 mm

### EMERGENCY

Rated duration	3 hours
Optional duration	1 / 2 / 4 / 8 hours (dependant on jumpers)
Emergency testing	Standalone Self test Wi-Fi Self test DALI Self test

### COMPLIANCE

Standards	IEC 60598-2-22 CISPR 15 IEC 62034 IEC 62386-201 EMC-2004/108/EC LVD-2006/95/EC
-----------	---

BATTERY		CHARGE	
Type	LiFePO <sub>4</sub>	Type	Smart charge
Voltage	6.4V	Time	16 Hours
Code	zc-batt-1500mah	Operation	Multi-state

CONSTRUCTION	
Body	PC
Diffuser	Acrylic
Gear tray	PC
Cut-out	305 x 65 mm

**NOTE:** For more information on the chemical resistance of our polycarbonate, please see our website.

## TOTAL POWER CONSUMPTION (TPC)

MAINTAINED MODE		NON-MAINTAINED MODE	
MAX.	AVG.	MAX.	AVG.
4.5 W	2.35 W	3 W	0.25 W

Datasheet is subject to change without notice, E&OE  
Last updated: 10 October 2018 \_V2.2