

CHOOSING THE CORRECT MODEL

Choosing the correct range is essential to ensure the requirements of your application are met

For example choosing a model with a higher service life will mean lower maintenance costs over the life of the product, or choosing a product with a higher emergency classification may mean that less units are required and therefore save on installation and servicing costs.

The following information can be used as a guide to select the correct model for your application.

| | BASIC | LITE | STANDARD | PRO |
|---|-------|------|----------|-----|
| LOOK | | | | |
| Standard form factor | | ✓ | ✓ | ✓ |
| Compact form factor | ✓ | | | |
| FEATURES | | | | |
| Long life electronics | ✓ | ✓ | ✓ | ✓ |
| Standard emergency features (SPU) | ✓ | ✓ | ✓ | ✓ |
| Self test (out of the box) | | | ✓ | ✓ |
| DALI (out of the box) | | | ✓ | ✓ |
| Lowest power consumption | | | ✓ | ✓ |
| 2 hour / 3 hour / 4 hour selectable | | | ✓ | ✓ |
| Non-maintained / maintained selectable | | | ✓ | ✓ |
| zencontrol wireless upgradable | | | ✓ | ✓ |
| zencontrol Cloud and app connectable | | | ✓ | ✓ |
| PERFORMANCE (LIGHT OUTPUT & EMERGENCY CLASS) | | | | |
| Standard (industry baseline) | ✓ | ✓ | | |
| Medium | | | ✓ | |
| High (best in class) | | | | ✓ |
| BATTERY | | | | |
| Lithium (LiFePO ₄) batteries | ✓ | ✓ | ✓ | ✓ |
| Battery service life (years) | 4 | 5 | 10 | 10 |
| Smart battery charger | | | ✓ | ✓ |

| RANGE | BASIC | LITE | STANDARD | PRO |
|--|--|--|--|--|
| TWINSPOT IP65 Black / white options  | |  2.7 W |  2.8 W - built to order |  5.5 W |
| CLAYMORE Sensor option 600 mm and 1200 mm Emergency / non-emergency  |  |  | |  |
| CLAYMORE IP65 Sensor option 600 mm and 1200 mm Emergency / non-emergency  |  |  | |  |
| PEARL Sensor option Emergency / non-emergency  |  IP20 Ø380 mm |  IP65 Ø350 and Ø450 mm |  IP65 Ø350 mm |  IP65 Ø450 mm |
| LED FIRE Cut-out sizes Ø44 / 84 / 140 mm Black / white options  |  |   |   |   |
| SURFACE MOUNT Black / white options  |  Circular |  Square |  Square | |
| BOXIT EXITS Wall mounted Ceiling mounted  |   | | | |
| MERCURY EXITS 300×150 mm decal IP65 case available Theatre black option  |  | |  | |
| SLIM EXITS 300×150 mm decal 200 × 100 mm decal Theatre black option  | | |  | |
| JUMBO EXITS 500 x 250 mm decal  |  | | |  |